

BTS-1000A

Bluetooth to Serial RS-232 Converter



Features

- ▶ Full Bluetooth 2.0 Support + EDR
- ▶ No External Software Needed
- ▶ Easy to Configure
- ▶ Supports Max Baudrate of 115.2 K bps, Min 1200 bps.
- ▶ Plug-In-Design, 5 V DC External Power Supply
- ▶ 300 ft. (Enhance Antenna) CLASS 1

Specifications

Bluetooth

Version 2.0 + EDR

Supported Bluetooth Profiles

Generic Access Profile, Serial Port Profile

Bluetooth Radio

Class 1

Serial Interface

RS-232 Female DSUB-9 Connector (RX / TX Crossed Over)

Power Connector

External Adapter with DC Jack 1.3 mm

Power Supply

5V DC / 200mA, Current Consumption 80 mA
Power over Pin-9

Operating Temperature

0° - 60°C

Storage Temperature

-15° - 70°C

External Antenna

2 dBi External Antenna, Reverse SMA Connector

Dimension (W x H x D)

65 x 12 x 30 mm (2.56 x 0.47 x 1.18 inches)

Weight

38g

Warranty

5-Year Warranty

Ordering Information

BTS-1000A

Bluetooth to Serial RS-232 Converter with Power Adapter & External Antenna