

# SP-150R039/040S

## Aluminum Front IP65 5 wire Resistive Touch Panel PC



### Feature

- ✓ Fanless design and compact solution
- ✓ 6th Gen Intel® Core™ Celeron/ i5/i7 CPU
- ✓ Resolution 1024 x 768 dpi
- ✓ 5 wires resistive touch solution
- ✓ IP65 Silver aluminum front bezel
- ✓ 4 x USB, 2 x GLAN, 1 x HDMI, 1 x DP++
- ✓ Panel mount & VESA mounting & Clips

System	
CPU	6th Gen Intel® Core™ Celeron 3955U i5-6300U/i7-6600U
Memory	2 x 204-pin DDR3L 1600MHz SODIMM up to 16 GB
H/W Monitor	
Watchdog Timer	256-Level Watchdog Timer
I/O Ports	
RS232	1
GLAN	2
USB	4
HDMI	1
DP++	1
Line-Out /MIC In	1
Storage	
Storage	1 x SATA 2.0 2.5" HDD/SSD
Expansion	
Mini-PCle	1 x Full-size (one w/ mSATA) 1 x Full-size
Power Requirement	
Power Input Voltage	DC in 12V for 039S or 15~36V for 040S
Touch Screen	
Touch screen	5-wire resistive
OS support	
Win Pro , 7,8,10, Embedded Win 7,8,10	

Display	
Size	15" TFT (4:3)
Resolution	1024 x 768
Colors	16.2 M
Luminance ( cd/m2)	400
Contrast Ratio	700:1
View Angle ( H / V )	160/160
Mechanical & Environmental	
Operation Temp	0 ~ 45°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	Clip mount, Panel mount & VESA mounting(100X100mm)
Dimension (W x H x D mm) &Weight	303.7 x 400.9 x 93(9kg)
Optional	
RS232/422/485	2
External antenna	1 or 2
Waterproof Sponge	1
Clip	10
Rack Mount Bezel	1
Magnetic Bezel	1
Optical Bonding	1
No Touch Screen	1
AR Glass	1

Optional High Brightness Panel					
Resolution	1024 x 768				
Color	16.2 M	16.7 M	16.7 M	16.2 M	16.7 M
Luminance(cd/m2)	2000	1600	1000	1000	800
Contrast Ratio	700:1	700:1	1700:1	700:1	700:1
Viewing Angle	160/160	160/160	170/170	160/160	160/160

\*Specifications are subject to change without notice.

Inspiring a Reliable Solution  
www.kingdy.com.tw

