

SP-215R039/040S

Aluminum Front IP65 5 wire Resistive Touch Panel PC



Feature

- ✓ Fanless design and compact solution
- ✓ 6th Gen Intel® Core™ Celeron/ i5/i7 CPU
- ✓ Resolution 1920 x 1080 dpi
- ✓ 5 wires resistive touch solution
- ✓ IP65 Silver aluminum front bezel
- ✓ 4 x USB, 2 x GLAN, 1 x HDMI, 1 x DP++
- ✓ Panel mount & VESA mounting & Clips

System	
CPU	6th Gen Intel® Core™ Celeron 3955U i5-6300U/i7-6600U
Memory	2 x 204-pin DDR3L 1600MHz SODIMM up to 16 GB
H/W Monitor	
Watchdog Timer	256-Level Watchdog Timer
I/O Ports	
RS232	1
GLAN	2
USB	4
HDMI	1
DP++	1
Line-Out /MIC In	1
Storage	
Storage	1 x SATA 2.0 2.5" HDD/SSD
Expansion	
Mini-PCle	1 x Full-size (one w/ mSATA) 1 x Full-size
Power Requirement	
Power Input Voltage	DC in 12V for 039S or 15~36V for 040S
Touch Screen	
Touch screen	5-wire resistive
OS support	
Win Pro , 7,8,10, Embedded Win 7,8,10	

Display	
Size	21.5" TFT (16:9)
Resolution	1920 x 1080
Colors	16.7 M
Luminance (cd/m2)	300
Contrast Ratio	3000:1
View Angle (H / V)	178/178

Mechanical & Environmental	
Operation Temp	0 ~ 45°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	Clip mount, Panel mount & VESA mounting(100X100mm)
Dimension (W x H x D mm) &Weight	581.3 x337.2 x 93.6(13.5kg)

Optional	
RS232/422/485	2
External antenna	1 or 2
Waterproof Sponge	1
Clip	10
Rack Mount Bezel	1
Magnetic Bezel	1
Optical Bonding	1
No Touch Screen	1
AR Glass	1

Optional High Brightness Panel	
Resolution	1920 x 1080
Color	16.7 M
Luminance(cd/m2)	1600
Contrast Ratio	900:1
Viewing Angle (H/V°)	178/178

*Specifications are subject to change without notice.