## *IP-215P039/040S*

## Full IP65 PCAP Touch Panel PC



## **Feature**

- ✓ Fanless design and compact solution
- √ 6th Gen Intel® Core™ Celeron/ i5/i7 CPU
- ✓ Resolution 1920 x 1080 dpi
- ✓ PCAP touch solution
- ✓ Full IP65 Stainless Steel Chassis
- ✓ All IP65 stainless connector
- ✓ 2 x USB, 2 x RS232, 2 x LAN
- ✓ VESA mounting & Clips

Display

System		
СРИ	6th Gen Intel® Core™ Celeron 3955U i5-6300U/i7-6600U	
Memory	2 x 204-pin DDR3L 1600MHz SODIMM up to 16 GB	
H/W Monitor		
Watchdog Timer	256-Level Watchdog Timer	
I/O Ports		
RS232	2	
GLAN	2	
USB	2	
Storage		
Storage	1 x SATA 2.0 2.5" HDD/SSD	
Expansion		
Mini-PCIe	1 x Full-size (one w/ mSATA) 1 x Full-size	
Power Requirement		
Power Input Voltage	DC in 12V for 039S or 15~36V for 040S	
Touch Screen		
Touch screen	PCAP	
OS support		
Win Pro , 7,8,10, Embedded Win 7,8,10		

Size	21.5" TFT (16:9)		
Resolution	1920 x 1080		
Colors	16.7 M		
Luminance ( cd/m2)	300		
Contrast Ratio	3000:1		
View Angle ( H / V )	178/178		
Mechanical & Environmental			
External Heat Sink	Back Side		
Operation Temp	0 ~ 45°C		
Storage Humidity	10 ~ 90%, non-condensing		
Mount	VESA mounting(100X100mm)		
Dimension (W x H x D mm) &Weight	607 x 401 x67.1 (13kg)		
Optional			
RS232/422/485	1		
External antenna	1 or 2		
Full IP65 Power Adaptor	1		
No Touch Screen	1		
AR Glass	1		
Optical Bonding	1		

Optional High Brightness Panel	
Resolution	1920 x 1080
Color	16.7 M
Luminance(cd/m2)	1600
Contrast Ratio	900:1
Viewing Angle (H/V°)	178/178

<sup>\*</sup>Specifications are subject to change without notice.

