

SP-150R004/005S

Aluminum Front IP65 5 wire Resistive Touch Panel PC



Feature

- ✓ Fanless design and compact solution
- ✓ Intel® Bay Trail Quad Core 2.0GHz CPU
- ✓ Resolution 1024 x 768 dpi
- ✓ 5 wires resistive touch solution
- ✓ IP65 Silver aluminum front bezel
- ✓ 4 x USB, 1 x VGA, 1 x LAN, 1 x RS232
- ✓ Panel mount & VESA mounting & Clips

System

CPU	Intel® Bay Trail D-J1900 2.0GHz Quad Core Processor (On Board)
Memory	1 x 204-pin DDR3L SODIMM up to 8 GB

H/W Monitor

Watchdog Timer	256-Level Watchdog Timer
----------------	--------------------------

I/O Ports

RS232	1
GLAN	1
USB	4 x USB2.0
VGA	1
Line-Out /MIC In	1

Storage

Storage	1 x SATA 2.0 2.5" HDD/SSD
---------	---------------------------

Expansion

Mini-PCIe	1 x Full-size (one w/ mSATA)
-----------	------------------------------

Power Requirement

Power Input Voltage	DC in 12V
---------------------	-----------

Touch Screen

Touch screen	5-wire resistive
--------------	------------------

OS support

Win Pro , 7,8,10, Embedded Win 7,8,10

Display

Size	15" TFT (4:3)
Resolution	1024 x 768
Colors	16.2 M
Luminance (cd/m2)	400
Contrast Ratio	700:1
View Angle (H / V)	160/160

Mechanical & Environmental

Operation Temp	0 ~ 45°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	Clip mount, Panel mount & VESA mounting(100X100mm)
Dimension (W x H x D mm) &Weight	303.7 x 400.9 x 93(9kg) 303.7 x 400.9 x 71 (10kg) for 005S

Optional

RS232	2
External antenna	1 or 2
Waterproof Sponge	1
Clip	10
Rack Mount Bezel	1
Magnetic Bezel	1
Optical Bonding	1
No Touch Screen	1
AR Glass	1
PCIe Slot	1 for High Chassis
Second Lan with 2 Memory slot (up to 8G)	1(004S)

Optional High Brightness Panel

Resolution	1024 x 768				
Color	16.2 M	16.7 M	16.7 M	16.2 M	16.7 M
Luminance(cd/m2)	2000	1600	1000	1000	800
Contrast Ratio	700:1	700:1	1700:1	700:1	700:1
Viewing Angle (H/V°)	160/160	160/160	170/170	160/160	160/160

*Specifications are subject to change without notice.

Inspiring a Reliable Solution

www.kingdy.com.tw

