

# SP-150R003S

## Aluminum Front IP65 5 wire Resistive Touch Panel PC



### Feature

- ✓ Fanless design and compact solution
- ✓ Intel® Bay Trail Quad Core 2.0GHz CPU
- ✓ Resolution 1024 x 768 dpi
- ✓ 5 wires resistive touch solution
- ✓ IP65 Silver aluminum front bezel
- ✓ 4 x USB, 1 x VGA, 1 x HDMI, 2 x LAN, 2 x COM
- ✓ Panel mount & VESA mounting & Clips

### System

CPU	Intel® Bay Trail D-J1900 2.0GHz Quad Core Processor (On Board)
Memory	2 x 204-pin DDR3L SODIMM up to 8 GB

### H/W Monitor

Watchdog Timer	256-Level Watchdog Timer
----------------	--------------------------

### I/O Ports

RS232	1
RS232/422/485	1
GLAN	2
USB	4
VGA	1
HDMI	1
Line-Out/In /MIC In	1

### Storage

Storage	1 x SATA 2.0 2.5" HDD/SSD
---------	---------------------------

### Expansion

Mini-PCIe	1 x Full-size (one w/ mSATA)
-----------	------------------------------

### Power Requirement

Power Input Voltage	DC in 12V /19V/24V
---------------------	--------------------

### Touch Screen

Touch screen	5-wire resistive
--------------	------------------

### OS support

Win Pro 7,8,10 ; Embedded Win 7, 8,10
---------------------------------------

### Display

Size	15" TFT (4:3)
Resolution	1024 x 768
Colors	16.2 M
Luminance ( cd/m2)	400
Contrast Ratio	700:1
View Angle ( H / V )	160/160

### Mechanical & Environmental

Operation Temp	0 ~ 45°C
Storage Humidity	10 ~ 90%, non-condensing
Mount	Clip mount, Panel mount & VESA mounting(100X100mm)
Dimension (W x H x D mm) & Weight	303.7 x 400.9 x 93(9kg)

### Optional

RS232	2
External antenna	1 or 2
Waterproof Sponge	1
Clip	10
Rack Mount Bezel	1
Magnetic Bezel	1
Optical Bonding	1
No Touch Screen	1
AR Glass	1
PCIe x 1 Slot	1

### Optional High Brightness Panel

Resolution	1024 x 768				
Color	16.2 M	16.7 M	16.7 M	16.2 M	16.7 M
Luminance(cd/m2)	2000	1600	1000	1000	800
Contrast Ratio	700:1	700:1	1700:1	700:1	700:1
Viewing Angle (H/V°)	160/160	160/160	170/170	160/160	160/160

\*Specifications are subject to change without notice.